CMOS Oscillator Provides -168 dBc-Hz Noise Floor

Crystek Corporation has launched the CCHD-575 [1], a new Ultra-Low Phase Noise CMOS Oscillator [2] providing a **-**168 dBc/Hz noise floor. The CCHD-575 is presented as the industry's lowest-jitter clock oscillator in a 5 x 7.5 mm package.

Crystek's CCHD-575 features a typical phase jitter of 82 fSec RMS at 100 MHz. Close-in phase noise is -90 dBc/Hz @ 10 Hz, while its floor is at -168 dBc/Hz. The extremely low phase noise performance is very useful in applications such as: DACs (digital-to-analog converters), ADCs (analog-to-digital converters), low phase signal sources, and test & measurement.

The CCHD-575 generates frequencies between 50MHz and 130MHz. Its output driver is capable of driving ±24mA, translating to a rise/fall time of ~600ps at 100 MHz with a 15pF load. Input supply voltage of 3.3Vdc consuming 15mA of current is required. Extended temperature operating range of -40°C to +85°C is also available.

The Crystek CCHD-575 CMOS Oscillator is made in the U.S.A. and available from Crystek's stocking distributors. For pricing details, contact Crystek Corporation.

Family datasheets are available for download at www.crystek.com [3].

For more information, contact sales at Crystek Corporation, 12730 Commonwealth Drive, Ft. Myers, FL 33913.
Tel: 800-237-3061 or 239-561-3311; Fax: 239-561-1025; E-mail: sales@crystek.com [4]

Source URL (retrieved on *11/25/2014 - 8:26pm*):
http://www.ecnmag.com/product-releases/2011/08/cmos-oscillator-provides-168-dbc-hz-noise-floor?qt-video_of_the_day=0

Links:
[1] http://www.crystek.com/crystal/spec-sheets/clock/CCHD-575.pdf
[2] http://www.crystekcrystals.com/crystal/clock/clock-hcmos.asp
[3] http://www.crystek.com
[4] mailto:sales@crystek.com