PoL DC/DC converters include 3-A and 5-A SIP packages

Murata Power Solutions announced the OKX Series of miniature non-isolated single output DC-to-DC converters designed for embedded point-of-load (PoL) applications. Within the OKAMI OKX Series there are four models that provide 3-A or 5-A outputs with either 5-V or 12-V nominal inputs. Complementing the existing OKY range of surface mounted PoL converters available from Murata Power Solutions, the new OKX-T/3 and OKX-T/5 series additions are packaged in a five-pin single-in-line package (SIP). Design engineers now have a choice of package format depending on available board space and application requirements. Measuring 22.9 m x 10.2 mm x 7.1 mm, the SIP package meets Distributed-Power Open Standards Alliance (DOSA) specifications and is designed as a drop-in replacement for other DOSA-compliant parts. These efficient converters, typically 94.5 percent at 3.3 Vout, and capable of driving ceramic capacitive loads up to 1,000 uF, have tight load regulation making them appropriate for powering applications such as FPGAs and DSPs. The output voltage is programmable from 0.75 V to 3.63 VDC for the 5-Vin part, and up to 5 VDC for the 12-Vin part. Input under voltage lockout, output short circuit, output over current, and over-temperature protection features are offered across the OKX series. The On/Off Control feature is also standard in either Positive or Negative logic. The converters have exceptional thermal derating performance and can operate in most environments from -40 to +85 degrees C. Typical applications include powering CPUs, datacom / telecom systems, server and storage equipment, industrial systems, and programmable logic and mixed voltage designs.

Murata Power Solutions
www.murata-ps.com [1]

Source URL (retrieved on *05/19/2013 - 11:37pm*):
http://www.ecnmag.com/product-releases/2012/05/pol-dc/dc-converters-include-3-and-5-sip-packages?qt-video_of_the_day=0

Links:
[1] http://www.murata-ps.com