Hull Roughness Control unit can be operated with one hand

Controlling the roughness of a ship’s hull plays an important role in the operating costs of a vessel. The roughness of a ship’s hull increases mainly due to corrosion, pitting, plate undulation, mechanical damage, dry spray and above all bio fouling. Proper maintenance and the correct application of The TQC Hull roughness Gauge consists of a Control unit with a menu-driven interface and a sensor unit.

The Hull Roughness Control unit can be operated with just one hand, a 4-way directional push button operates an intuitive menu on a large illuminated display. The neck strap keeps the users’ hands free when required.

The Sensor unit is equipped with three non-slip wheels and a carbide tipped stylus and is moved over the ship’s hull in a horizontal way collecting series of measurements. A set of LED’s indicate the status of the instrument so operation is possible without observing the control unit.

Statistics, time/date and location of each series and the average hull roughness are automatically calculated and stored in the Control unit. Using the supplied USB-cable and software you instantly create inspection reports in Microsoft Excel. Your own company logo and or -details can be incorporated to restyle your reports.

Technical Data

Accuracy:	+/- 5 microns or <2%, whichever is greater
Memory:	Enough for 4 complete surveys done both in- and out-docking, totalling over 10,000 readings
Location storage:	Simply point and click the hull location in the displayed graphical representation of the ship's hull
Units:	Microns
Speed:	50 mm/s, with speed indication LED in the Sensor unit
Interface:	USB serial to PC connection
Power supply:	4 AA type Alkaline Cells, available worldwide

Dimensions and Weight

Sensor Depth:	205mm	Control unit Depth:	7.9" (200mm)
Sensor Width:	80mm	Control unit Width:	4.5" (115mm)
Sensor Height:	40mm	Control unit Height:	1.6" (40mm)
Sensor Weight:	630g approx.	Control unit Weight:	350g approx

The Hull Roughness Gage comes complete with:

- Hull Roughness Control Unit with neck-strap
- Hull Roughness Sensor Cable
- USB thumb drive with software
- 4 x AA batteries
- Hull Roughness Sensor
- DC9015 Calibration plate
- USB connection cable for PC

SU-892010 DC9000 Hull Roughness Gage $4658.00

Paul N. Gardner Co., Inc., www.gardco.com [1], (954) 946-9454, 1-800-762-2478

Source URL (retrieved on *05/22/2013 - 11:15am*):
http://www.ecnmag.com/product-releases/2012/10/hull-roughness-control-unit-can-be-operated-one-hand?qt-recent_content=0

Links:
[1] http://www.gardco.com