

## Flange-mounted USB 2.0 connectors deliver reliable protection for harsh environments

CONEC has expanded its bayonet-locking, IP67-rated industrial USB 2.0 connector series utilizing a 4-hole flange mount nickel plated die-cast housing. The water-resistant USB 2.0 connectors can be mounted on the front or rear side of enclosure panels up to 3.2mm thick. The interface of the USB 2.0 connector meets IP67-rating requirements when mated or covered with a protective cap. The addition of four-hole mounting provides extra protection against harsh environment elements, while facilitating easier “on-the-fly” connections for industrial applications.



The USB 2.0 connector also features M28 threads as an additional connection method to bayonet locking. The industrial-rated USB 2.0 connector operates within a temperature range of -40°C to +80°C, with a 1.5A maximum current rating at 25°C. The voltage handling of the rugged USB connector is 100VDC. The nickel plated die-cast outer body is RoHS compliant.

For more information on the flange mount USB 2.0 connectors, visit [www.conec.com](http://www.conec.com) [1]; email [info@conec.com](mailto:info@conec.com) [2]; or call 919-460-8800.

**Source URL (retrieved on 01/24/2015 - 10:55pm):**

[http://www.ecnmag.com/product-releases/2013/01/flange-mounted-usb-20-connectors-deliver-reliable-protection-harsh-environments?qt-video\\_of\\_the\\_day=0](http://www.ecnmag.com/product-releases/2013/01/flange-mounted-usb-20-connectors-deliver-reliable-protection-harsh-environments?qt-video_of_the_day=0)

**Links:**

[1] <http://www.conec.com>

## **Flange-mounted USB 2.0 connectors deliver reliable protection for harsh en**

Published on Electronic Component News (<http://www.ecnmag.com>)

---

[2] <mailto:info@conec.com>