Mini modem supports 3.1Mbps downlink rate



Telit Wireless Solutions announced

the introduction of the DE910-DUAL Mini PCle for commercial and industrial computer markets. The mini PCle form factor has become a popular standard adopted by connected device manufacturers to easily integrate wireless connectivity into their devices. North America's first full-featured EV-DO mini PCle modem, supports 3.1Mbps downlink rates and 1.8Mbps uplink rates. In addition, it is fully compatible with its HSPA+ counterpart-- the HE910 Mini PCle providing connected device makers maximum range of options for cellular operator support with one product design. Equipped with a high performance, multi-constellation GPS plus GLONASS receiver, the DE910-DUAL Mini PCle card provides superior navigation coverage in harsh environments and challenging urban canyons, making it ideally suited for devices such as mobile computers, mobile resource management (MRM) terminals, digital signage, and point of sale devices.

Telit's DE910-DUAL Mini PCIe includes distinguishing features such as extended operating temperature range and Rx diversity which allows the end-device to be equipped with two distinct cellular antennas improving the quality and reliability of the wireless connectivity in urban areas, undergrounds, and other similar scenarios, and making the product ideal for applications such as wireless backup for DSL modems and gateways. Fully voice capable, the DE910 mini PCIe provides full-duplex PCM input and output (not available through the mini PCIe edge connector) for applications such as voice gateways, fleet management and rugged phones. For easy integration, the product includes device drivers for most Windows platforms, Linux and Android and, is available for all major CDMA carriers and partner networks in North America.

The DE910 Mini PCIe is available with a range of development tools and associated documentation. Integrators in application areas requiring higher security and encrypted data transmission such as financial, medical, POS, and others can also make use of the product's embedded SSL protocol and supporting development

Mini modem supports 3.1Mbps downlink rate

Published on Electronic Component News (http://www.ecnmag.com)

tools.

Telit Wireless Solutions www.telit.com [1] +39 040 4192 111

Source URL (retrieved on 05/21/2013 - 7:49am):

http://www.ecnmag.com/products/2012/10/mini-modem-supports-31mbps-downlink-rate

Links:

[1] http://www.telit.com