Power supplies are 80 PLUS and EN/UL/IEC 60601-1 3rd Edition Certified



Tumbler Technologies +

TRUMPower offers its TMPC 1U Series of 250-W to 350-W AC/DC medical grade PC power supplies with 1.59" low profile. The units are approved to the 3rd edition of EN 60601-1, UL 60601-1, and IEC 60601-1 medical standards, which includes risk management and are also approved to EN/UL/IEC 60950-1 2nd edition standards. The power supplies have DC output voltages and maximum loads of +3.3 V/16 A, +5 V/18 A, +12 V1/16 A, +12 V2/16 A, -12 V/0.5 A, -5 V/0.2 A, +5 Vsb/2.5 A. Maximum loads for +3.3 V/+5 V/+12 V1/+12 V2 are 231 W, 281 W, and 331 W for the 250 W, 300 W, and 350 W models, respectively. The series is 80 PLUS Bronze certified, with an active efficiency of 80 percent minimum at full load. Measured at 7.48" x 3.94" x 1.59", the power supplies come with an on/off switch, a thermally controlled low noise ball-bearing fan, and are furnished with a standard output cableset, which includes the 20+4 pins ATX motherboard connector, 4-pin or 8-pin +12V CPU connectors, SATA drive connectors, etc. that can meet the requirements of most PC-related applications.

With a 90-264 VAC universal input and active PFC, all models comply with EN61000-3-2 standards. The units meet ATX12V & EPS1U 2.0 standards and are CE marked, RoHS compliant. In addition, the power supplies meet EN60601-1-2 EMC standards, including EN55011/FCC/VCCI class B (conducted and radiated emissions), EN61000-3-2, EN61000-4-2, EN61000-4-3, EN61000-4-5, EN61000-4-11. Before delivery, the power supplies have passed 100% Burn-in test @ 50°C and 100% Hi-Pot test. Depending on the model, the calculated MTBF at full load ranges between 135K hours and 198K hours at 25°C ambient, per MIL-HDBK-217F. The earth leakage current at 264 VAC is 160µA typically.

The units feature dual input line fuses, 2 x MOPP (means of patient protection),

Power supplies are 80 PLUS and EN/UL/IEC 60601-1 3rd Edition Certified

Published on Electronic Component News (http://www.ecnmag.com)

output overvoltage, overload and short circuit protections. Overload protection is 150% maximum of the rated output. Hold up time is 17 milliseconds minimum at full load, nominal input voltage and power fail signal delay time is 1 millisecond minimum. The power supplies operate between 0° C to $+50^{\circ}$ C and can be stored at -20° C to $+80^{\circ}$ C.

Tumbler Technologies + TRUMPower

408-988-6622, <u>www.trumpower.com</u> [1]

Source URL (retrieved on 04/19/2014 - 8:47am):

http://www.ecnmag.com/products/2012/10/power-supplies-are-80-plus-and-en/ul/iec-60601-1-3rd-edition-certified?qt-recent_content=0

Links:

[1] http://www.trumpower.com